



# WANLI

EXPERIENCE PERFORMANCE YOU CAN FEEL





# TABLE OF CONTENTS

***SPORT MACRO*** ALL-SEASON PERFORMANCE, TOURING, CUV PAGES 4 - 7

---

***RANGE TOUR H/T*** HIGHWAY SUV, LIGHT TRUCK, COMM VAN PAGES 8 - 10

---

***RANGE POWER A/T3*** ALL-TERRAIN SUV, LIGHT TRUCK, FLOTATION PAGES 11-13

---

***RANGE R/T*** RUGGED-TERRAIN SUV, LIGHT TRUCK, FLOTATION PAGES 14 -15

---

***ECO SENDERO M/T2*** MUD-TERRAIN LIGHT TRUCK, FLOTATION PAGES 16 -17

---

***RANGE M/T2*** MUD-TERRAIN LIGHT TRUCK, FLOTATION PAGES 18 -19

---

**LIMITED PROTECTION POLICY**

PAGES 20 - 21





# WANLI

**Wanli Tire** is a performance-driven tire brand built on precision engineering, modern design, and dependable value. Positioned to compete aggressively in high-demand replacement segments, Wanli delivers products that balance handling, durability, and price integrity – without compromising on technical credibility.

## TIRE MATRIX

### *PASSENGER / COMMUTER*



### *CUV / SUV / LIGHT TRUCK*



# SPORT MACRO

The **Sport Macro** is engineered for drivers who expect sharp response and confident control year-round. Built for late-model sedans, coupes, and performance CUVs, it delivers a balance of precision handling and everyday comfort your customers will appreciate. performance with a quiet and comfortable ride.



## FEATURES & BENEFITS

- The asymmetrical pattern provides performance tuned from the inside-to-outside. The higher density inner siping provides wet and light snow traction; while the outside provides excellent dry handling and cornering stability. Asymmetric tread patterns allow for cross-rotation to maximize tread life.
- The computer optimized multi-radius profile is designed for vehicles requiring responsive handling and cornering stability.
- Wide circumferential grooves and variable density siping improves traction in wet and light snow conditions.

**50k**

Mile Limited  
Tread Wear

**155**

Sizes  
14" to 26"



All-Season

# SPORT MACRO



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
185/60R14	82H	SL	9.00	22.76	7.44	1047@44	500AA	WLC10240
175/65R14	82T	SL	9.00	22.99	6.97	1047@44	500AA	WLC10200
185/65R14	86H	SL	15.37	32.52	12.52	1168@44	500AA	WLC10220
175/70R14	88T	XL	12.85	32.36	11.69	1235@49	500AA	WLC10100
185/70R14	88T	SL	15.37	34.53	12.52	1235@44	500AA	WLC10120
195/70R14	91T	SL	15.37	31.81	9.25	1356@44	500AA	WLC10140
205/70R14	95H	SL	15.75	34.53	12.52	1521@44	500AA	WLC10160
205/70R14	98H	XL	15.75	34.53	12.52	1655@44	500AA	WLC10180
185/55R15	82V	SL	12.85	31.46	11.50	1047@44	500AA	WLC10555
195/50R15	82V	SL	15.37	36.54	12.52	1047@44	500AA	WLC10595
195/55R15	85V	SL	9.50	23.43	7.91	1135@44	500AA	WLC10575
185/60R15	84H	SL	15.37	32.52	12.52	1102@44	500AA	WLC10485
195/60R15	88H	SL	15.37	29.29	8.78	1235@44	500AA	WLC10505
205/60R15	91V	SL	9.50	24.69	8.23	1356@44	500AA	WLC10525
175/65R15	84H	SL	9.00	23.98	6.97	1102@44	500AA	WLC10375
185/65R15	92H	XL	15.37	34.53	12.52	1389@49	500AA	WLC10395
195/65R15	91H	SL	15.37	28.86	9.25	1356@44	500AA	WLC10415
205/65R15	94H	SL	15.37	31.89	11.18	1477@44	500AA	WLC10435
205/70R15	96T	SL	15.37	34.09	10.98	1565@44	500AA	WLC10305
215/65R15	100T	XL	10.00	26.02	8.70	1764@49	500AA	WLC10455
215/70R15	98T	SL	15.37	34.57	12.32	1655@44	500AA	WLC10325
225/70R15	100T	SL	10.71	28.86	9.25	1764@44	500AA	WLC10345
185/55R16	87H	XL	12.85	32.80	11.93	1201@49	500AA	WLC10835
195/45R16	84V	XL	15.37	34.53	12.52	1102@49	500AA	WLC11000
195/55R16	91V	XL	9.50	24.41	7.91	1356@49	500AA	WLC10855
205/45ZR16	87W	XL	15.37	30.55	9.76	1201@49	500AA	WLC11020
205/50R16	87V	SL	15.37	31.50	9.76	1201@44	500AA	WLC10950
225/50ZR16	92W	SL	10.71	28.43	8.98	1389@44	500AA	WLC10975
205/55R16	94V	XL	9.50	24.88	8.43	1477@49	500AA	WLC10875
215/55R16	97H	XL	10.00	25.28	8.90	1609@49	500AA	WLC10895
225/55R16	99V	XL	10.71	29.09	9.45	1709@49	500AA	WLC10915
205/60R16	96V	XL	9.50	25.67	8.23	1565@49	500AA	WLC10765
215/60R16	95V	SL	10.00	26.14	8.70	1521@44	500AA	WLC10785
225/60R16	98H	SL	10.00	26.61	8.98	1655@44	500AA	WLC10815
205/65R16	95H	SL	9.50	26.46	8.23	1521@44	500AA	WLC10685

# SPORT MACRO



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTOG	Stock#
215/65R16	102H	XL	10.00	27.01	8.70	1874@49	500AA	WLC10705
225/65R16	100H	SL	10.71	28.98	9.45	1764@44	500AA	WLC10725
235/65R16	107T	XL	10.00	28.03	9.45	2149@49	500AA	WLC10745
205/70R16	97H	SL	10.00	27.32	8.23	1609@44	500AA	WLC10665
205/40ZR17	84W	XL	15.37	31.73	9.25	1102@49	500AA	WLC11470
245/40ZR17	95W	XL	12.60	31.81	9.25	1521@49	500AA	WLC11520
205/45ZR17	88W	XL	15.37	30.47	9.76	1235@49	500AA	WLC11360
215/45ZR17	91W	XL	10.00	24.65	8.39	1356@49	500AA	WLC11380
225/45ZR17	94W	XL	10.00	24.96	8.86	1477@49	500AA	WLC11400
235/45ZR17	97Y	XL	10.00	25.35	9.29	1609@49	500AA	WLC11420
245/45ZR17	99W	XL	12.60	31.50	9.76	1709@49	500AA	WLC11440
205/50R17	93V	XL	9.50	25.12	8.43	1433@49	500AA	WLC11260
215/50ZR17	95W	XL	10.00	25.51	8.90	1521@49	500AA	WLC11290
225/50ZR17	98W	XL	10.00	25.91	9.17	1655@49	500AA	WLC11310
235/50ZR17	100W	XL	10.00	26.30	9.65	1764@49	500AA	WLC11330
205/55R17	95V	XL	9.50	25.91	8.43	1521@49	500AA	WLC11165
215/55R17	98V	XL	15.37	33.94	11.77	1655@49	500AA	WLC11185
225/55R17	101V	XL	10.00	26.77	9.17	1819@49	500AA	WLC11205
235/55ZR17	103W	XL	10.00	27.17	9.65	1929@49	500AA	WLC11225
235/60R17	102H	SL	10.49	28.11	9.45	1874@44	500AA	WLC11115
255/35ZR18	94Y	XL	10.71	30.00	9.45	1477@49	500AA	WLC12020
215/40ZR18	89Y	XL	15.37	32.36	11.69	1279@49	500AA	WLC11920
225/40ZR18	92Y	XL	10.00	25.08	9.06	1389@49	500AA	WLC11940
235/40ZR18	95W	XL	8.50	25.39	9.49	1521@49	500AA	WLC11960
245/40ZR18	97Y	XL	10.00	25.71	9.76	1609@49	500AA	WLC11980
255/40ZR18	99Y	XL	10.00	26.02	10.24	1709@49	500AA	WLC12000
215/45ZR18	89W	SL	15.37	32.56	11.50	1279@44	500AA	WLC11795
215/45ZR18	93W	XL	15.37	32.56	11.50	1279@44	500AA	WLC11815
225/45ZR18	95Y	XL	10.00	25.94	8.86	1521@49	500AA	WLC11835
235/45ZR18	98W	XL	10.00	26.34	9.29	1655@49	500AA	WLC11855
245/45ZR18	100Y	XL	10.00	26.65	9.57	1764@49	500AA	WLC11875
255/45ZR18	103W	XL	17.64	31.54	11.42	1929@49	500AA	WLC11895
225/50ZR18	99W	XL	10.00	26.89	9.17	1709@49	500AA	WLC11715
235/50ZR18	101W	XL	10.00	27.28	9.65	1819@49	500AA	WLC11735
245/50ZR18	100W	SL	10.71	27.76	9.17	1764@44	500AA	WLC11755

# SPORT MACRO



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
215/55R18	99V	XL	10.00	27.28	8.90	1709@49	500AA	WLC11570
225/55R18	98V	SL	10.00	27.76	9.17	1655@44	500AA	WLC11590
235/55R18	104V	XL	10.00	28.15	9.65	1984@49	500AA	WLC11610
245/55ZR18	103W	SL	10.00	28.62	9.96	1929@44	500AA	WLC11650
255/55ZR18	109W	XL	10.00	29.02	10.43	2271@49	500AA	WLC11670
265/30ZR19	93Y	XL	17.64	36.54	13.58	1433@49	500AA	WLC12675
275/30ZR19	96W	XL	16.00	30.51	10.71	1565@49	500AA	WLC12695
225/35ZR19	88Y	XL	15.37	31.65	10.71	1235@49	500AA	WLC12505
235/35ZR19	91Y	XL	10.71	29.53	9.76	1356@49	500AA	WLC12525
245/35ZR19	93Y	XL	10.00	25.79	9.76	1433@49	500AA	WLC12545
255/35ZR19	96Y	XL	10.71	29.69	9.96	1565@49	500AA	WLC12565
275/35ZR19	100Y	XL	10.00	26.57	10.94	1764@49	500AA	WLC12605
225/40ZR19	93Y	XL	10.71	27.87	8.70	1433@49	500AA	WLC12375
235/40ZR19	96Y	XL	10.00	26.42	9.49	1565@49	500AA	WLC12395
245/40ZR19	98Y	XL	10.00	26.73	9.76	1655@49	500AA	WLC12415
255/40ZR19	100Y	XL	10.00	27.05	10.24	1764@49	500AA	WLC12435
275/40ZR19	105Y	XL	10.00	27.68	10.94	2039@49	500AA	WLC12475
225/45ZR19	96W	XL	10.71	28.50	8.98	1565@49	500AA	WLC12250
235/45R19	99V	XL	10.00	27.36	9.29	1709@49	500AA	WLC12300
245/45ZR19	102W	XL	10.00	27.68	9.57	1874@49	500AA	WLC12330
255/45ZR19	104W	XL	10.00	28.07	10.04	1984@49	500AA	WLC12350
235/50R19	103V	XL	10.00	28.31	9.65	1929@49	500AA	WLC12140
255/50ZR19	107Y	XL	10.00	29.09	10.43	2149@49	500AA	WLC12190
225/55R19	99V	SL	10.00	28.78	9.17	1709@44	500AA	WLC12045
235/55R19	105V	XL	10.00	29.17	9.65	2039@49	500AA	WLC12065
245/55R19	103V	SL	10.00	29.65	9.96	1929@44	500AA	WLC12085
255/55R19	111V	XL	10.00	30.04	10.43	2403@49	500AA	WLC12105
225/30ZR20	85W	XL	15.37	32.52	12.52	1135@49	500AA	WLC13590
245/30ZR20	90Y	XL	10.71	32.99	10.98	1323@49	500AA	WLC13620
275/30ZR20	97Y	XL	16.00	30.55	10.71	1609@49	500AA	WLC13660
285/30ZR20	99Y	XL	10.00	26.77	11.42	1709@49	500AA	WLC13680
305/30ZR20	103Y	XL	15.75	32.52	12.52	1929@49	500AA	WLC13710

---

# ***RANGE TOUR H/T***

The **Range Tour H/T** is purpose-built for SUVs, crossovers, and light-duty pickups that spend most of their time on pavement. It delivers consistent highway comfort with the durability needed for heavier vehicles and daily commuting.



## **FEATURES & BENEFITS**

- Balanced 5-rib pattern with coupled shoulder elements provides enhanced response, handling, and support for heavy loads with resistance to irregular wear.
- Optimized pitch sequence reduces tread pattern noise for a quiet ride.
- Wide circumferential grooves and zig-zag siping improves traction in wet and light snow conditions

**50K**

Mile Limited  
Tread Wear

**59**

Sizes  
15" to 20"



All-Season

# RANGE TOUR H/T



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
235/75R15	109T	XL	10.50	27.36	9.29	2271@49	500AA	WLC22005
235/65R16	107T	XL	10.50	25.47	9.49	2149@49	500AA	WLC22385
215/70R16	100H	SL	10.33	25.75	9.17	1764@44	500AA	WLC22205
225/70R16	103T	SL	10.33	26.61	8.98	1929@44	500AA	WLC22235
235/70R16	106T	SL	10.33	27.40	9.49	2094@44	500AA	WLC22255
245/70R16	107T	SL	10.50	28.35	9.29	2149@44	500AA	WLC22275
255/70R16	111T	SL	10.50	30.16	9.65	2403@44	500AA	WLC22295
265/70R16	112T	SL	10.33	26.77	9.76	2469@44	500AA	WLC22315
245/75R16	111T	SL	10.33	26.30	9.65	2403@44	500AA	WLC22105
215/60R17	100H	XL	10.50	25.91	9.17	1764@49	500AA	WLC22820
225/60R17	99H	SL	10.33	26.77	9.17	1709@44	500AA	WLC22840
235/60R17	102T	SL	10.50	27.44	8.98	1874@44	500AA	WLC22860
215/65R17	99T	SL	10.33	26.89	9.17	1709@44	500AA	WLC22630
225/65R17	102H	SL	10.33	28.78	9.17	1874@44	500AA	WLC22650
235/65R17	104H	SL	10.33	25.39	9.49	1984@44	500AA	WLC22670
245/65R17	107H	SL	10.33	26.34	9.29	2149@44	500AA	WLC22690
255/65R17	110T	SL	10.50	28.15	9.65	2337@44	500AA	WLC22710
265/65R17	112T	SL	10.33	27.83	9.76	2469@44	500AA	WLC22730
275/65R17	115T	SL	10.33	27.72	9.76	2679@44	500AA	WLC22750
P235/70R17	105T	SL	10.33	28.07	10.04	2040@44	500AA	WLC22485
245/70R17	110T	SL	10.33	28.31	9.65	2337@44	500AA	WLC22515
255/70R17	112T	SL	10.33	27.17	9.65	2469@44	500AA	WLC22535
265/70R17	115H	SL	10.50	27.76	9.76	2679@44	500AA	WLC22575
265/70R17	115T	SL	10.50	27.76	9.76	2679@44	500AA	WLC22555
P225/55R18	97H	SL	10.50	27.01	10.24	1610@44	500AA	WLC23290
235/55R18	100V	SL	10.50	27.48	8.98	1764@44	500AA	WLC23320
225/60R18	100H	SL	10.50	27.76	9.17	1764@44	500AA	WLC23130
235/60R18	107V	XL	10.50	27.60	9.49	2149@49	500AA	WLC23150
245/60R18	105H	SL	10.50	25.35	9.29	2039@44	500AA	WLC23170
255/60R18	112H	XL	10.50	27.28	9.65	2469@49	500AA	WLC23190
265/60R18	114H	XL	10.50	25.83	9.76	2601@49	500AA	WLC23210
235/65R18	106V	SL	10.50	26.42	9.49	2094@44	500AA	WLC22980
255/65R18	111T	SL	10.50	29.17	9.65	2403@44	500AA	WLC23010
265/65R18	114T	SL	10.50	25.79	9.76	2601@44	500AA	WLC23030
275/65R18	116T	SL	10.50	25.67	9.57	2756@44	500AA	WLC23050
255/70R18	113T	SL	10.50	28.11	9.45	2535@44	500AA	WLC22880
265/70R18	116T	SL	10.50	24.72	9.76	2756@44	500AA	WLC22900

# RANGE TOUR H/T



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
P235/45R19	95H	SL	10.50	26.02	10.24	1710@49	500AA	WLC24440
P235/50R19	99H	SL	10.50	27.05	10.24	1710@44	500AA	WLC24390
235/55R19	105V	XL	10.33	28.03	10.24	2040@49	500AA	WLC24340
P255/60R19	109H	SL	10.33	29.09	10.43	2270@44	500AA	WLC24290
P245/50R20	102V	SL	10.50	29.06	10.04	1875@44	500AA	WLC24740
P235/55R20	102V	SL	10.50	27.05	10.04	1875@44	500AA	WLC24590
265/50R20	111V	XL	10.33	28.03	9.45	2403@49	500AA	WLC24790
275/55R20	117H	XL	10.33	25.71	9.76	2833@49	500AA	WLC24690
275/60R20	115H	SL	10.50	26.73	9.76	2679@44	500AA	WLC24540
LT215/85R16		E/10	10.33	26.65	9.57		-	WLC24890
LT225/75R16		E/10	10.33	27.68	9.57		-	WLC25030
LT245/75R16		E/10	10.33	29.65	9.96		-	WLC25080
LT265/75R16		E/10	10.33	28.07	10.24		-	WLC25130
LT235/85R16		E/10	10.33	29.69	9.96		-	WLC24950
LT245/70R17		E/10	12.50	27.68	9.96		-	WLC25330
LT265/70R17		E/10	10.33	30.08	10.43		-	WLC25430
LT245/75R17		E/10	12.50	28.62	9.96		-	WLC25230
LT235/80R17		E/10	10.33	28.66	9.57		-	WLC25180
LT275/65R18		E/10	10.33	30.08	10.24		-	WLC25580
LT275/70R18		E/10	12.50	26.02	10.24		-	WLC25530
LT275/65R20		E/10	12.50	25.00	10.24		-	WLC27330
235/65R16C		E/10	10.33	26.46	9.49		-	WLC28330

---

# ***RANGE POWER A/T3***

The **Range Power A/T3** is built for customers who split time between pavement and the trail. It balances daily drivability with aggressive off-road capability – a true dual-purpose A/T.



## **FEATURES & BENEFITS**

- Aggressive chevron tread pattern provides excellent traction both on- and off-road with biting edges designed for soft surfaces like mud, dirt, sand, and silt.
- High-density siping improves traction in wet conditions while maintaining element stability for off-road durability.
- Coupled tread elements improve stability and durability when off-road.

**50k**  
Mile Limited  
Tread Wear

**69**  
Sizes  
15" to 24"



All-Season

# RANGE POWER A/T3



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
215/75R15	100T	SL	12.50	27.68	8.50	1764@44	600AA	WLC32430
235/75R15	109S	XL	10.33	25.31	10.67	2271@49	600AA	WLC32480
265/75R15	112T	SL	10.33	26.57	10.94	2469@44	600AA	WLC32530
245/70R16	107T	SL	10.33	28.31	10.67	2149@44	600AA	WLC32750
255/70R16	111T	SL	12.50	30.08	10.24	2403@44	600AA	WLC32780
265/70R16	112T	SL	12.50	30.63	10.71	2469@44	600AA	WLC32810
275/70R16	114S	SL	10.33	32.87	11.18	2601@44	600AA	WLC32840
245/75R16	111S	SL	12.50	30.47	9.76	2403@44	600AA	WLC32630
265/75R16	116T	SL	10.33	27.56	10.94	2756@44	600AA	WLC32660
225/65R17	102H	SL	12.50	28.50	8.98	1874@44	600AA	WLC32980
245/65R17	107S	SL	12.50	29.53	9.76	2149@44	600AA	WLC33010
265/65R17	112S	SL	12.50	30.55	10.71	2469@44	600AA	WLC33040
275/65R17	115T	SL	12.50	31.10	10.98	2679@44	600AA	WLC33070
245/70R17	110T	SL	10.33	29.33	10.67	2337@44	600AA	WLC32910
265/70R17	115T	SL	10.33	26.54	10.94	2679@44	600AA	WLC32940
235/60R18	107T	XL	12.50	29.09	9.45	2149@49	600AA	WLC33335
245/60R18	105H	SL	12.50	29.57	9.76	2039@44	600AA	WLC33355
265/60R18	110H	SL	12.50	30.51	10.71	2337@44	600AA	WLC33405
265/60R18	110T	SL	12.50	30.51	10.71	2337@44	600AA	WLC33385
285/60R18	120T	SL	12.50	31.46	11.50	3086@44	600AA	WLC33435
265/65R18	114T	SL	12.50	31.54	10.71	2601@44	600AA	WLC33220
275/65R18	116T	SL	10.33	30.87	11.18	2756@44	600AA	WLC33240
265/70R18	116T	SL	10.33	30.55	10.94	2756@44	600AA	WLC33120
275/55R20	117H	XL	10.33	27.68	10.94	2833@49	600AA	WLC33570
285/55R20	116T	XL	10.33	27.87	11.42	2756@49	600AA	WLC33590
275/60R20	115T	XL	10.33	29.76	10.75	2679@44	600AA	WLC33485
275/60R20	116H	XL	10.33	29.76	10.75	2679@44	600AA	WLC33505
285/45R22	114H	XL	10.33	26.77	11.42	2601@49	600AA	WLC33635
305/45R22	118T	XL	12.50	32.80	11.93	2910@49	600AA	WLC33685
285/40R24	112H	XL	12.50	32.99	11.42	2469@49	600AA	WLC33885
LT235/75R15	104/101S	C/6	15.00	28.86	9.25	1985/1820@50	-	WLC34035
LT265/70R16	121/118S	E/10	12.85	29.09	9.45	3195/2910@80	-	WLC34345
LT305/70R16	124/121S	E/10	12.85	32.99	10.98	3525/3195@65	-	WLC34395
LT225/75R16	115/112S	E/10	10.33	33.23	12.32	2680/2470@80	-	WLC34155
LT245/75R16	120/116S	E/10	10.33	28.66	12.60	3042/2778@80	-	WLC34205
LT265/75R16	123/120S	E/10	12.85	29.57	9.76	3415/3085@80	-	WLC34235
LT285/75R16	126/123R	E/10	15.00	32.83	11.26	3750/3415@80	-	WLC34285
LT315/75R16	127/124S	E/10	15.00	34.57	12.32	3860/3525@65	-	WLC34315
LT215/85R16	115/112S	E/10	15.00	30.39	8.50	2680/2470@80	-	WLC34085
LT235/85R16	120/116S	E/10	10.33	31.61	12.32	3042/2778@80	-	WLC34115
LT305/65R17	121/118S	E/10	12.85	32.99	10.98	3195/2910@65	-	WLC35325
LT245/70R17	119/116S	E/10	10.33	32.80	11.93	3000/2755@80	-	WLC34865

# RANGE POWER A/T3



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
LT265/70R17	121/118S	E/10	15.00	31.65	10.71	3195/2910@80	-	WLC34915
LT285/70R17	126/123Q	E/10	12.85	30.63	10.71	3750/3415@80	-	WLC34965
LT245/75R17	121/118S	E/10	9.83	25.35	8.23	3195/2910@80	-	WLC34645
LT255/75R17	111/108S	C/6	15.00	32.05	10.04	2405/2205@50	-	WLC34675
LT235/80R17	120/117R	E/10	10.33	28.43	12.32	3085/2835@80	-	WLC34545
LT275/65R18	123/120S	E/10	12.85	30.55	9.76	3415/3085@80	-	WLC35655
LT285/65R18	125/122S	E/10	15.00	32.56	11.50	3640/3305@80	-	WLC35705
LT265/70R18	124/121S	E/10	12.85	28.86	9.25	3525/3195@80	-	WLC35525
LT275/70R18	125/122S	E/10	15.00	33.19	10.98	3640/3305@80	-	WLC35575
LT285/75R18	129/126Q	E/10	15.00	34.84	11.26	4080/3750@80	-	WLC35425
LT275/55R20	120/117S	E/10	12.85	29.53	9.76	3085/2835@80	-	WLC36075
LT285/55R20	122/119S	E/10	12.85	30.51	10.71	3305/3000@80	-	WLC36125
LT305/50R20	117/114S	E/10	15.00	32.05	12.44	2835/2600@65	-	WLC36235
LT305/55R20	121/118S	E/10	12.85	31.89	11.18	3195/2910@65	-	WLC36175
LT265/60R20	121/118S	E/10	12.85	28.50	8.98	3195/2910@80	-	WLC35885
LT275/60R20	123/120S	E/10	12.85	29.53	9.76	3415/3085@80	-	WLC35935
LT285/60R20	125/122S	E/10	15.00	33.46	11.50	3640/3305@80	-	WLC35985
LT295/60R20	126/123R	E/10	15.00	33.94	11.77	3750/3415@80	-	WLC36035
LT275/65R20	126/123S	E/10	15.00	34.33	10.98	3750/3415@80	-	WLC35785
31X10.50R15LT	109S	C/6	10.33	30.98	11.42	2270@50	-	WLC36535
35X12.50R17LT	121R	E/10	12.85	32.09	10.98	3195@65	-	WLC36735
35X12.50R18LT	123R	E/10	10.33	31.26	11.69	3415@65	-	WLC36835
33X12.50R20LT	114R	E/10	10.33	32.09	11.22	2600@65	-	WLC36935
35X12.50R20LT	125R	F/12	15.00	34.53	12.52	3640@80	-	WLC37035
37X12.50R20LT	126Q	E/10	15.00	36.54	12.52	3750@65	-	WLC37135
33X12.50R22LT	109S	E/10	10.33	30.08	11.22	2270@65	-	WLC37435
35X12.50R22LT	121R	F/12	15.00	34.53	12.52	3195@80	-	WLC37515
37X13.50R24LT	124Q	F/12	15.00	36.54	13.58	3525@80	-	WLC37635

---

# ***RANGE R/T***

The Range R/T is built to dominate rugged terrain and return to pavement with stable, responsive on-road handling – the ideal balance of trail toughness and street control.



## **FEATURES & BENEFITS**

- The aggressive dual pitch pattern provides excellent off-road performance in mud, dirt, gravel, and other soft surfaces.
- Self-cleaning tread with integrated stone ejectors keeps the small rocks out to help maintain traction in soft surfaces.

**40k**

Mile Limited  
Tread Wear

**37**

Sizes  
16" to 24"



All-Season

# RANGE R/T



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
LT325/60R20	126/123Q	E/10	15.00	35.35	13.03	3750/3415@80	-	WLC46205
35X12.50R18LT	123Q	E/10	9.45		7.44	3415@65	-	WLC46475
35X12.50R18LT	128Q	F/12	9.45		7.44	3415@65	-	WLC46525
33X12.50R20LT	114Q	E/10	15.00	32.52	12.52	2600@65	-	WLC46575
33X12.50R20LT	123R	F/12	15.00	32.52	12.52	2600@65	-	WLC46625
35X12.50R20LT	121Q	E/10	9.45		7.44	3195@65	-	WLC46675
35X12.50R20LT	125Q	F/12	9.45		7.44	3195@65	-	WLC46725
35X12.50R20LT	125R	F/12	9.45		7.44	3195@65	-	WLC46775
37X12.50R20LT	128Q	F/12	15.00	36.54	12.52	3970@80	-	WLC46825
37X13.50R20LT	127Q	E/10	9.83		7.91	3860@65	-	WLC46875
33X12.50R22LT	109Q	E/10	15.00	32.52	12.52	2270@65	-	WLC46925
33X12.50R22LT	114Q	F/12	15.00	32.52	12.52	2270@65	-	WLC46975
35X12.50R22LT	121Q	F/12	9.83		7.91	3195@80	-	WLC47025
37X13.50R22LT	128Q	F/12	15.00	36.54	13.58	3970@80	-	WLC47075
35X12.50R24LT	120Q	F/12	15.00	34.53	12.44	2755@80	-	WLC47125
37X13.50R24LT	124Q	F/12	15.00	36.54	13.58	3525@80	-	WLC47175
LT325/45R24	124S	F/12	15.00	35.51	12.83	3860/3525@80	-	WLC46425

# ECO SENDERO M/T2

The Eco Sendero M/T2 is designed for serious off-roaders demanding maximum traction in extreme conditions – mud, rock, gravel, sand, and debris-heavy terrain.

## FEATURES & BENEFITS

- Durable 3-ply construction\* protects the tire from the many off-road hazards such as gravel and debris. And provides additional sidewall puncture resistance.
- Self-cleaning tread with integrated stone ejectors keeps the small rocks out to help maintain traction in soft surfaces.
- The deep, functional buttress elements provide additional biting edges for improved traction in soft surfaces.



# ECO SENDERO M/T2

Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
LT235/75R15	104/101Q	C/6	17.00	29.09	9.25	1985/1820@50	-	WLC54225
LT265/70R16	117/114Q	D/8	18.50	30.87	10.71	2835/2600@65	-	WLC54385
LT245/75R16	120/116Q	E/10	17.00	30.71	9.76	3042/2778@80	-	WLC54255
LT265/75R16	123/120Q	E/10	15.50	31.89	10.51	3000/2755@65	-	WLC54285
LT285/75R16	126/123R	E/10	18.50	33.07	11.26	3750/3415@80	-	WLC54315
LT265/65R17	120/117Q	E/10	18.50	30.79	10.71	3085/2835@80	-	WLC54545
LT265/70R17	121/118Q	E/10	18.50	31.89	10.71	3195/2910@80	-	WLC54415
LT285/70R17	121/118Q	E/10	18.50	32.99	11.50	3195/2910@80	-	WLC54445
LT295/70R17	121/118Q	E/10	18.50	33.54	11.77	3195/2910@80	-	WLC54475
LT285/65R18	125/122Q	E/10	18.50	32.80	11.50	3640/3305@80	-	WLC54645
LT275/65R20	126/123Q	E/10	18.50	34.33	10.98	3750/3415@80	-	WLC54745
30X9.50R15LT	104Q	C/6	17.00	29.76	9.45	1985@50	-	WLC54845
31X10.50R15LT	109Q	C/6	17.00	30.75	10.55	2270@50	-	WLC54945
32X11.50R15LT	113Q	C/6	18.50	31.77	11.42	2535@50	-	WLC55045
33X12.50R15LT	108Q	C/6	18.50	32.76	12.52	2205@35	-	WLC55145
35X12.50R17LT	121Q	E/10	20.50	34.76	12.52	3195@65	-	WLC55245
33X12.50R18LT	118Q	E/10	20.50	32.76	12.52	2910@65	-	WLC55345
35X12.50R18LT	123Q	E/10	20.50	34.76	12.52	3415@65	-	WLC55445
33X12.50R20LT	114Q	E/10	20.50	32.76	12.52	2600@65	-	WLC55545
35X12.50R20LT	121Q	E/10	20.50	34.76	12.52	3195@65	-	WLC55645
37X13.50R20LT	127Q	E/10	20.50	36.77	13.58	3860@65	-	WLC55745
33X12.50R22LT	109Q	E/10	20.50	32.76	12.52	2270@65	-	WLC55845
35X12.50R22LT	117Q	E/10	20.50	34.76	12.52	2835@65	-	WLC55945
37X13.50R22LT	123Q	E/10	20.50	36.77	13.58	3415@65	-	WLC56045
37X13.50R24LT	120Q	E/10	20.50	36.77	13.58	3085@65	-	WLC56145

---

# ***RANGE M/T2***

The **Range M/T2** delivers uncompromising off-road traction for trucks and SUVs built to leave pavement behind.



## **FEATURES & BENEFITS**

- Durable 3-ply construction\* protects the tire from the many off-road hazards such as gravel and debris. And provides additional sidewall puncture resistance.
- Self-cleaning tread with integrated stone ejectors keeps the small rocks out to help maintain traction in soft surfaces.
- The deep, functional buttress elements provide additional biting edges for improved traction in soft surfaces.



# RANGE M/T2



Size	LI/SR	LR/PR	Tread Depth	Overall Diameter	Section Width	Max Load @ PSI	UTQG	Stock#
265/60R18	110S	SL				2337@44	-	WLC63945
LT265/75R16	119/116Q	E/10				3000/2755@80	-	WLC64545
LT265/75R16	123/120Q	E/10				3415/3085@80	-	WLC64645
LT315/75R16	127/124Q	E/10	15.50	34.57	12.32	3860/3525@65	-	WLC64745
LT235/85R16	120/116Q	E/10	10.00		8.70	3042/2778@80	-	WLC64445
LT245/75R17	121/118Q	E/10	10.00		8.70	3195/2910@80	-	WLC64945
LT235/80R17	120/117Q	E/10	10.00		8.70	3085/2835@80	-	WLC64845
LT265/60R18	119/116Q	E/10	15.50	30.51	10.71	3000/2755@80	-	WLC65345
LT275/65R18	123/120Q	E/10	10.00		9.06	3415/3085@80	-	WLC65245
LT275/70R18	125/122Q	E/10	15.50	33.19	10.98	3640/3305@80	-	WLC65045
LT305/70R18	126/123Q	E/10	15.50	34.84	12.24	3750/3415@65	-	WLC65145
LT285/50R20	119/116R	E/10	10.00		9.06	3000/2755@80	-	WLC65745
LT275/55R20	120/117Q	E/10	10.00		9.06	3085/2835@80	-	WLC65545
LT305/55R20	121/118Q	E/10	10.00		8.86	3195/2910@65	-	WLC65645
LT295/65R20	129/126Q	E/10	15.50	35.12	11.77	4080/3750@80	-	WLC65445
37X13.50R18LT	128Q	E/10	17.00	36.54	13.58	3970@65	-	WLC65845
33X12.50R24LT	104Q	E/10	10.00		8.86	1985@65	-	WLC66145

# WANLI TIRES

## LIMITED PROTECTION POLICY

Thank you for your interest in Wanli brand tires for your vehicle. We are proud of the quality and performance of the wide range of Wanli products and we understand that your continued satisfaction is essential to our success.

### ELIGIBILITY

This Limited Protection Policy applies to Wanli brand passenger, light truck and specialty trailer tires purchased on or after January 1, 2020, or, in the absence of proof of purchase, tires with a manufacturing DOT code reading DOT 0120 or later. Eligible tires are covered by this Limited Protection Policy for up to 60 months from the date of purchase or tire manufacturer date. This Limited Protection Policy applies to the original owner of new Wanli branded passenger, light truck and specialty trailer tires that are operated in normal service and used on the same vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. Only Wanli tires purchased and operated in the United States and Canada are covered by this Limited Protection Policy. For Wanli branded product purchased thru an online retailer, a tire claim must go back to the original selling Wanli dealer. The online retailer where the Americus branded product was purchased would need to facilitate the claim with that authorized Americus dealer on the consumer's behalf.

### WHAT IS COVERED BY OUR EXCLUSIVE NO QUESTIONS ASKED, 25/365 FREE REPLACEMENT LIMITED PROTECTION POLICY?

The Wanli No Questions Asked, 25/365 Free Replacement Limited Protection Policy will fully cover (100% credit) all eligible Wanli brand passenger, light truck and specialty trailer tires should one become unserviceable due to defective workmanship, materials, road hazard or a condition other than those listed below during the first 25% of usable treadwear or one year from date of purchase, whichever occurs first.

Tires not eligible for the No Questions Asked, 25/365 Free Replacement Limited Protection Policy that are removed from service due to a covered condition will be replaced with a comparable new Wanli brand tire on a prorated basis for a period up to 60 months from the date of purchase or tire manufacturer date, or when the treadwear indicators become visible (worn to 2/32"), whichever occurs first.

### WHAT IS A COMPARABLE TIRE?

A comparable tire may be either the same line and pattern of tire or, in the event that the tire is not available, a tire of the same construction and quality with a different sidewall or tread configuration. If a higher priced tire is accepted as replacement, the difference in price will be at an additional charge to the owner. Any Americus brand replacement tire provided pursuant to this Limited Protection Policy will be covered by the Americus Limited Protection Policy in effect at the time of replacement.

### MILEAGE COVERAGE PLAN

If an eligible tire wears down to the treadwear indicator bars (2/32") and the tire has not delivered the miles specified below, Wanli will provide a prorated adjustment based on actual mileage delivered. The cost of mounting, balancing and any other service charges including applicable taxes are excluded from reimbursement.

Pattern	Coverage Plan (Miles/Km)	Road Hazard 25/365	Workmanship & Materials (Mo.)
Sport Macro	50,000/80,000	Yes	60
Range Tour H/T	50,000/80,000	Yes	60
Range Power A/T3	50,000/80,000	Yes	60
Range R/T	40,000/65,000	Yes	60
Eco Sendero M/T2	N/A	Yes	60
Range M/T2	N/A	Yes	60



# WANLI

The Mileage Coverage Plan applies only to the original purchaser and the tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. The Mileage Coverage Plan does not apply to tires used in commercial applications. Tires that have not been rotated at least every 6,000 miles as evidenced by a completed rotation schedule are excluded. Likewise, tires in service for more than 60 months regardless of mileage attained are excluded.

#### **WHAT IS NOT COVERED BY THIS LIMITED PROTECTION POLICY?**

- Improper operation or maintenance. This includes, but is not limited to, effects caused by improper tire inflation and/or improper load/speed practices and/or improper or insufficient tire rotation.
- Wear due to improper vehicle alignment including but not limited to, uneven, cupping, irregular, spotty and feathering wear
- Deliberate abuse or vandalism
- Ride or vibration complaint after the first 1/32" of treadwear
- Damage due to snow chain usage, improper mounting/dismounting or automotive accident
- Tires used in commercial applications are not eligible for 25/365 or Mileage coverage where applicable.

#### **OWNER'S OBLIGATIONS**

To make an eligible claim under this Limited Protection Policy, tires must be rotated with the prescribed rotation patterns as recommended by either the vehicle owner's manual or an authorized Wanli tire dealer. Owner must present an original tire sales invoice indicating the date of purchase, tire description and odometer mileage. Adjustment tires must be presented to an authorized Wanli dealer and those tires replaced become the property of Wanli Tires. Installation charges such as mounting, dismounting and balancing, as well as, any applicable taxes and government-mandated charges on the services rendered at the time of adjustment is the owner's responsibility. Adjustment claims must be completed on an approved claim form, supplied by an authorized Wanli dealer, and submitted at time of adjustment.

#### **WHAT ARE YOUR LEGAL RIGHTS?**

No Representative or Dealer has authority to make any representation, promise or agreement on behalf of Americus, except as stated herein.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the tire manufacturer. Under no circumstances is this Limited Protection Policy a representation that a tire failure cannot occur. This Limited Protection Policy gives you specific legal rights and you may also have other rights that vary from state to state or province to province.

#### **DISCLAIMER**

This Limited Protection Policy is in lieu of, and Wanli Tires hereby disclaims, any and all other Limited Protection Policies and representations, express or implied, including without limitation any Protection Policy of merchantability of fitness for a particular purpose, and no other Limited Protection Policy or representation of any kind is made by Wanli Tires or shall be implied by law. This Limited Protection Policy is subject to change without notice.

#### **LIMITATION OF DAMAGES**

In no event and under no circumstance shall WanliTires be liable to the buyer for any indirect, special, incidental, consequential, lost profit, loss of business, loss of goodwill or reputation, punitive or other damage, cost (including for replacement transportation), expense or loss of any kind. Some states and provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

#### **AMERICUS TIRE CARE AND MAINTENANCE GUIDE**

Proper inflation pressure is essential for optimum tire performance, safety, and fuel economy. Check for proper inflation pressure at least monthly while tires are cool, as tires will warm up from use after several miles so it is best to check before driving. Use a quality handheld accurate air pressure gauge. It is best to occasionally have your Wanli tires inspected by a professional tire shop, as it is difficult to tell just by looking at radial tires whether they are under-inflated or over-inflated. Furthermore, when operating a vehicle equipped with radial tires, it is difficult to notice when a tire has gone flat or nearly flat since the handling of the vehicle may not deteriorate significantly. Remember to always maintain inflation pressure at the level recommended by the vehicle manufacturer as shown on the vehicle placard, on the vehicle certification label or in the vehicle owner's manual.

Evidence of air loss or repeated under-inflation always requires expert inspection to determine the source of leakage and tire removal to determine reparability. To avoid injury, NEVER attempt to re-inflate a tire that has been in operation severely under-inflated. Progressive air loss may result from a variety of conditions such as punctures, cuts, curbing, impacts or partial bead unsealing. Some installation


or fitment causes for air loss are (1) incomplete bead seating, (2) tearing of the tire bead caused by a machine tool due to insufficient lubrication or improper adjustment, and (3) leaking valve core or rubber valve components. These should be corrected or replaced when problems are detected and/or whenever tires are replaced.

Under-inflation is the leading cause of tire failure and may result in severe cracking, component separation or complete loss of air. Under-inflation reduces tire load carrying capacity, allows for excessive sidewall flexing and increases rolling resistance, resulting in potential heat build-up and mechanical damage. Maintaining proper inflation pressure is the most important thing you can do to help promote tire safety, durability and maximize tread life.

Over-inflation will deteriorate ride quality, reduce braking ability and generate unwanted vibration. Over-inflation also increases the chances of impact damage.

#### **DON'T OVERLOAD YOUR VEHICLE**

The maximum load capacity stamped on the sidewalls of P-metric tires is reduced by ten percent when used on a light truck, utility vehicle or trailer. Never fit P-metric tires to light trucks that specify LT-type replacement tires.



**Scan the QR code or visit  
the URL below to view  
the complete warranty  
information on the Wanli**





***WANLITIRES.COM***



**WANLI**

***American Omni Trading Company***

***1221 Park West Green Dr. | Katy, TX 77493***

***Corporate Phone | 281-600-TIRE***

***American-Omni.com***